1440

Protector

Top Loader Case

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- · Strong polyurethane wheels with stainless steel bearings
- · Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Comfortable rubber over-molded handle
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Retractable extension trolley handle
- · Stainless steel padlock protectors



CONFIGURATIONS



1440 Standard



1444 With Utility Padded Divider Set With Padded Office Divider Set & Lid Organizer



1447 & Lid Organizer



1440NF No Foam



1440WF With Foam

DIMENSIONS

17.10 x 7.50" x 16.00 (43.4 x 19.1 x 40.6 cm) Interior (L×W×D) 19.70 x 12.00" x 18.00 (50 x 30.5 x 45.7 cm) Exterior (L×W×D)

Lid Depth 2.00" (5.1 cm) **Bottom Depth** 14.00" (35.6 cm) **Total Depth** 16" (40.6 cm) **Int Volume** 1.19 ft3 (0.034 m3) Padlock Hole Diameter 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS **O-Ring** Polymer **Pins** Stainless Steel **Foam** 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 16.50 lbs (7.5 kg)

 Weight Empty
 14.50 lbs (6.6 kg)

 Buoyancy
 95.30 lbs (43.2 kg)

 Master Pack Weight
 18.00 lbs (8.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes

ACCESSORIES



1441 6 pc. Replacement Foam Set



1443 Replacement O-ring



1448Photographer's Lid Organizer



1506TSA TSA Lock



1500D Desiccant Silica Gel

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-05-25