# 1620 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican<sup>™</sup> Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 4 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors



# CONFIGURATIONS



1620 Standard



1624 With Padded Dividers



**1620NF** No Foam



1620WF With Foam

## DIMENSIONS

Interior (L×W×D)	21.48 x 16.42" x 12.54 (54.6 x 41.7 x 31.9 cm)
Exterior (L×W×D)	24.76 x 19.57" x 13.90 (62.9 x 49.7 x 35.3 cm)
Lid Depth	2.01" (5.1 cm)
Bottom Depth	10.53" (26.7 cm)
Total Depth	12.54" (31.9 cm)
Int Volume	2.56 ft <sup>3</sup> (0.072 m <sup>3</sup> )
Padlock Hole Diameter	0.31" (0.8 cm)

#### MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

### COLOURS

Black

Desert Tan

OD Green

#### WEIGHT

Weight With Foam	24.62 lbs (11.2 kg)
Weight Empty	21.20 lbs (9.6 kg)
Buoyancy	149.91 lbs (68 kg)
Master Pack Weight	26.90 lbs (12.2 kg)

#### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

#### CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41

## OTHER

heels	2
ctendable Handle	yes
aster Pack	1
ameplate	yes
ilitary	yes

## ACCESSORIES



1609 Lid Organizer



6 pc. Replacement Foam Set



**1622** Pick N Pluck<sup>™</sup> Sections Only (set of 4)



1623 Replacement O-ring



1610MP EZ-Click<sup>™</sup> MOLLE Panel



1625 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock





1500D

Desiccant Silica Gel

Document created on 05-05-25