1595 Air

Designed for the professional adventurer, the 1595 Air case is perfect for those who need a little extra space without compromising on durability or weight. Sized between our popular 1535 Air carry-on case and the larger 1615 Air check-in case, the 1595 Air case offers the ideal solution for travelers seeking a lightweight and reliable option for their gear. Pelican[™] Air cases are the toughest and lightest cases Pelican has to offer. Each Pelican Air case is up to 40 percent lighter than an average polymer case yet still extremely durable. Pelican Air cases will lighten the load, while protecting your valued possessions. With Pelican's trusted protection, you can travel with confidence.

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- · Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
 *Check with your airline for exact measurement requirements
- Press and Pull[™] Latches
- Super-light proprietary HPX²[™] Polymer up to 40% lighter
- Waterproof O-ring seal
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- · Limited Lifetime Warranty (Where applicable by law)
- Mid-size airline check-in case*



CONFIGURATIONS



1595 Standard



1595NF No Foam



1595WF With Foam



1595TP With TrekPak Divider System



1595WD With Padded Dividers

DIMENSIONS

Interior (L×W×D)	25.53 x 14.92" x 8.92 (64.8 x 37.9 x 22.7 cm)
Exterior (L×W×D)	28.52 x 17.89" x 10.73 (72.4 x 45.4 x 27.3 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	6.92" (17.6 cm)
Total Depth	8.92" (22.7 cm)
Int Volume	1.97 ft ³ (0.056 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Pins	Stainless Steel

Foam	Polyurethane
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

Weight With Foam	16.35 lbs (7.4 kg)
Weight Empty	13.60 lbs (6.2 kg)
Buoyancy	148.37 lbs (67.3 kg)
Weight With Organizers	16.10 lbs (7.3 kg)

TEMPERATURE

Minimum Temperature	-60°F (-51.1 °C)
Maximum Temperature	160°F (71.1 °C)

ACCESSORIES



1500D Desiccant Silica Gel





1500CI Corrosion Intercept Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 05-03-25