1400 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- Watertight, crushproof, and dustproof
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- · Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware
- Stainless steel padlock protectors



CONFIGURATIONS



1400 Standard



1400NF No Foam



1400WF With Foam

DIMENSIONS

Interior (L×W×D)	11.81 x 8.87" x 5.18 (30 x 22.5 x 13.2 cm)
Exterior (L×W×D)	13.37 x 11.62" x 6.00 (34 x 29.5 x 15.2 cm)
Lid Depth	1.18" (3 cm)
Bottom Depth	4.00" (10.2 cm)
Total Depth	5.18" (13.2 cm)
Int Volume	0.31 ft ³ (0.009 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

Weight With Foam	4.41 lbs (2 kg)
Weight Empty	3.97 lbs (1.8 kg)
Buoyancy	20.06 lbs (9.1 kg)
Master Pack Weight	22.60 lbs (10.3 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67 MIL C-4150J Def Stan 81-41 ATA 300

OTHER

ACCESSORIES



1401 3 pc. Replacement Foam Set



1506TSA TSA Lock



1403 Replacement O-ring



1500D Desiccant Silica Gel



1400PF Special Application Panel Frame



1500Cl Corrosion Intercept Kit



1400TPKIT TrekPak Case Divider Kit



1507 Quick Mounts - set of 4

Document created on 05-03-25