



1520

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors



CONFIGURATIONS



1520
Standard



1524
With Padded Dividers



1526
With Convertible Travel Bag



1520NF
No Foam



1520WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 18.06 x 12.89" x 6.72 (45.9 x 32.7 x 17.1 cm) |
| Exterior (L×W×D) | 19.78 x 15.77" x 7.41 (50.2 x 40.1 x 18.8 cm) |
| Lid Depth | 1.79" (4.5 cm) |
| Bottom Depth | 4.93" (12.5 cm) |
| Total Depth | 6.72" (17.1 cm) |
| Int Volume | 0.91 ft³ (0.026 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|--------------------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLORS

| | | | |
|--|--|--|--|
|  Black |  Desert Tan |  Orange |  Silver |
|  Yellow | | | |

WEIGHT

| | |
|--------------------|---------------------|
| Weight With Foam | 9.35 lbs (4.2 kg) |
| Weight Empty | 8.29 lbs (3.8 kg) |
| Buoyancy | 63.00 lbs (28.6 kg) |
| Master Pack Weight | 23.30 lbs (10.6 kg) |

TEMPERATURE

| | |
|---------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| |
|----------------|
| IP67 |
| MIL C-4150J |
| Def Stan 81-41 |

OTHER

| | |
|-------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| 1508 Photographer's Lid Organizer | 1509 Lid Organizer | 1521 3 pc. Replacement Foam Set | 1523 Replacement O-ring | 1525 Padded Divider Set |
|  |  |  |  |  |
| 1520TPKIT TrekPak Case Divider Kit | 1520TPDIV Extra TrekPak Dividers | 1507 Quick Mounts - set of 4 | 1506TSA TSA Lock | 1500D Desiccant Silica Gel |



1520PF
Special Application Panel
Frame



1500CI
Corrosion Intercept Kit

Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com

Document created on 05-03-25