# 1550

### **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican  $^{\text{TM}}$  Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Personalized nameplate service available
- · Watertight, crushproof, and dustproof
- 2 level Pick N Pluck<sup>™</sup> with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Comfortable rubber over-molded handle
- Easy open double-throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



### **CONFIGURATIONS**



**1550** Standard



1550NF No Foam



**1550TP**With TrekPak Divider System



With Padded Dividers



1550WF

### **DIMENSIONS**

Interior (L×W×D) 18.63 x 14.18" x 7.72 (47.3 x 36 x 19.6 cm)

Exterior (L×W×D) 20.66 x 17.20" x 8.40 (52.5 x 43.7 x 21.3 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 5.87" (14.9 cm)

 Total Depth
 7.62" (19.4 cm)

 Int Volume
 1.18 ft³ (0.033 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

#### **MATERIALS**

**Body** Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

**Purge Vent** 3 Micron Hydrophobic Non-Woven

### **COLORS**

■ Black Orange Silver

### WEIGHT

 Weight With Foam
 11.90 lbs (5.4 kg)

 Weight Empty
 10.58 lbs (4.8 kg)

 Buoyancy
 69.89 lbs (31.7 kg)

 Master Pack Weight
 28.35 lbs (12.9 kg)

### **TEMPERATURE**

**Minimum Temperature** -40°F (-40 °C) **Maximum Temperature** 210°F (98.9 °C)

### **CERTIFICATIONS**

IP67 MIL C-4150J Def Stan 81-41 ATA 300

## **OTHER**

Master Pack2NameplateyesMilitaryyes

### **ACCESSORIES**



**1551** 4 pc. Replacement Foam Set



**1552**Pick N Pluck™ Sections Only (set of 2)



**1553** Replacement O-ring



Yellow

**1555** Padded Divider Set



**1550PF**Special Application Panel Frame



**1550TPKIT** TrekPak Case Divider Kit



**1510TPDIV** Extra TrekPak Dividers



**1507** Quick Mounts - set of 4



**1506TSA** TSA Lock



**1500D** Desiccant Silica Gel



### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 05-03-25