1120 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Watertight, crushproof, and dustproof

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1120 Standard



1120NF No Foam



1120WF With Foam

DIMENSIONS

| Interior (L×W×D) | 7.29 x 4.78" x 3.33 (18.5 x 12.1 x 8.5 cm) |
|-----------------------|--|
| Exterior (L×W×D) | 8.41 x 6.76" x 3.87 (21.4 x 17.2 x 9.8 cm) |
| Lid Depth | 0.50" (1.3 cm) |
| Bottom Depth | 2.56" (6.5 cm) |
| Total Depth | 3.06" (7.8 cm) |
| Int Volume | 0.07 ft ³ (0.002 m ³) |
| Padlock Hole Diameter | 0.19" (0.5 cm) |
| | |

MATERIALS

| Body | Polypropylene |
|------------|--------------------------------|
| Latch | Polypropylene |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

×

COLORS



WEIGHT

| Weight With Foam | 1.43 lbs (0.6 kg) |
|--------------------|--------------------|
| Weight Empty | 1.34 lbs (0.6 kg) |
| Master Pack Weight | 10.45 lbs (4.7 kg) |

TEMPERATURE

| Minimum Temperature | -40°F (-40 °C) |
|---------------------|-----------------|
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

| IP67 | |
|----------------|--|
| Def Stan 81-41 | |

OTHER

| Master Pack | 6 |
|-------------|-----|
| Military | yes |

ACCESSORIES



1121 3 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1123 Replacement O-ring



1506TSA TSA Lock



1120PF Special Application Panel Frame



1500D Desiccant Silica Gel



1120TPDIV Extra TrekPak Dividers



1500Cl Corrosion Intercept Kit



1120TPKIT TrekPak Case Divider Kit

 Pelican

 23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

 sales@pelican.com
 • www.pelican.com

Document created on 05-03-25